## **SAMSUNG QM5 H45 QM5 2.0 DCI (127 KW) AWD H45** (2008-2015)



ENGINE M9R Capacity: 7,4 liter (Service fill), Filter capacity: 0,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Meganza LSP 5W-30		
Change every 30000 km/12 months		

DIFFERENTIAL (4x4)
Capacity: 0-0 liter (Between min and max.)

USE

Normal

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

DIFFERENTIAL (4x4)
Capacity: 0-0 liter (Between min and max.)

CLIMATE
Moderate

Moderate

TRANSAXLE CVT FK0 1/1	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4016	

TRANSAXLE MANUAL ND5 6/1 Capacity: 1,8-2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	Gearlube RPC 75W-80		

SP Gear 5015	Gearlube RPC 75W-80		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Normal		Moderate	
USE		CLIMATE	
<b>TRANSAXLE MANUAL</b> ND8 6/1 Capacity: 2 liter			

## **SAMSUNG QM5 H45 QM5 2.0 DCI (127 KW) AWD H45** (2008-2015)



HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Check every 30000 km/ 12 months, change eve	ery 120000 km/ 48 months

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 12 months/ 30000 km	

COOLING SYSTEM Capacity: 8,5 liter (+ automatic transmission/transaxle), Capacity: 8 liter (+ manual transmission/transaxle)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 16	
Check every 12 months/ 30000 km	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.