
## **SSANGYONG KYRON KYRON M320 4WD**





ENGINE G32D/M162.990 Capacity: 9 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 15000 km/ 12 months		·
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 5W-30	Presteza MSP 5W-30	Avanza RPC 5W-30
Change every 15000 km/ 12 months		
USE		CLIMATE
First change only		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 10000 km		
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 5W-30	Presteza MSP 5W-30	Avanza RPC 5W-30
Change every 10000 km		•

DIFFERENTIAL FRONT WITH INTEGRATED OIL PAN Capacity: 0,78 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
Check every 15000 km/ 12 months		

DIFFERENTIAL REAR Capacity: 1,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
Check every 15000 km/ 12 months		

## **SSANGYONG KYRON KYRON M320 4WD**

(2007-2014)



<b>DIFFERENTIAL REAR LIGHT DUTY</b> Capacity: 1,8 liter	
use Normal	LIMATE loderate
PRODUCT RECOMMENDATION 1  Gearlube GL-5 80W-90	

Check every 15000 km/ 12 months

DIFFERENTIAL REAR RIGID AXLE Capacity: 2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	
Check every 15000 km/ 12 months	,

TRANSFERBOX
Capacity: 1,1-1,4 liter

USE

Normal

PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION 2

ATF Almirol

ATF Dexron II-D

Check every 15000 km/ 12 months, change every 60000 km/ 48 months

TRANSMISSION AUTOMATIC DC5 5/1 Capacity: 8 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Check every 12 months/ 30000 km		
USE	CLIMATE	
Severe	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change every 60000 km		

## **SSANGYONG KYRON KYRON M320 4WD**

(2007-2014)



HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and m	ax.)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
01 04 11			

Change every 24 months

POWER STEERING Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D
Check every 15000 km/ 12 months		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		
Check every 15000 km/ 12 months	•	

COOLING SYSTEM Capacity: 11,5-12 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Change every 200000 km/ 60 mon	ths	

## AIRCONDITIONING SYSTEM Capacity: 620-680 grams

Capacity: 020 cco gramo

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.