

BMC AUSTIN MORRIS J4 J4 DIESEL (1960-1965)

**ENGINE 15Z**

Capacity: 4,69 liter, Filter capacity: 0,71 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Classic Multigrade 10W-30	Classic Monograde 30

Change every 5000 km/ 150 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	
HDX 10W	

*Change every 5000 km/ 150 hours***DIFFERENTIAL REAR**

Capacity: 1,13 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Classic Gear EP 90	

Check every 5000 km/ 150 hours, change every 10000 km/ 300 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	
Classic Gear EP 80	

*Check every 5000 km/ 150 hours, change every 10000 km/ 300 hours***TRANSMISSION MANUAL 4/1**

Capacity: 2,55 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Classic Multigrade 10W-30	Classic Monograde 30

Check every 5000 km/ 150 hours, change every 10000 km/ 300 hours

BMC AUSTIN MORRIS J4 J4 DIESEL (1960-1965)**HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 5000 km/ 150 hours

COOLING SYSTEM

Capacity: 6,82 liter (+ heater)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -26		

Change every 12 months

BMC AUSTIN MORRIS J4 J4 DIESEL (1960-1965)



STEERING BOX

Capacity: 0,28 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90

Check every 5000 km/ 150 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80

Check every 5000 km/ 150 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.