## ATLAS GMBH WHEELED LOADERS 4WD 42E DEUTZ F3L-1011F (1994-1998)



| ENGINE Deutz F3L-1011F                           |  |                     |
|--|--|---------------------|
| USE<br>Name of                                   |  | CLIMATE             |
| Normal   |  | Moderate            |
| PRODUCT RECOMMENDATION 1  Dieselfleet CD+ 15W-40 | PRODUCT RECOMMENDATION 2  Multifleet SHPD 15W-40 |                     |
|  | Multineet of it D 13W-40                         |                     |
| Change every 250 hours/ 3 months                 |  | O. MAATE            |
| Initial service                                  |  | climate<br>Moderate |
| PRODUCT RECOMMENDATION 1                         | PRODUCT RECOMMENDATION 2                         |                     |
| Dieselfleet CD+ 15W-40                           | Multifleet SHPD 15W-40                           |                     |
| Change every 50 hours                            |  |                     |
|  |  |                     |
| DIFFERENTIAL FRONT                               |  |                     |
| USE  |  | CLIMATE             |
| Normal   |  | Moderate            |
| PRODUCT RECOMMENDATION 1                         |  |                     |
| Gearlube LS 80W-90                               |  |                     |
| Change every 1500 hours/ 12 months               | S  |                     |
| USE  |  | CLIMATE             |
| Initial service                                  |  | Moderate            |
| PRODUCT RECOMMENDATION 1                         |  |                     |
| Gearlube LS 80W-90                               |  |                     |
| Change every 500 hours                           |  |                     |
|  |  |                     |
| DIFFERENTIAL REAR                                |  |                     |
| Normal   |  | climate<br>Moderate |
|  |  | IVIOUETALE          |
| PRODUCT RECOMMENDATION 1  Gearlube LS 80W-90     |  |                     |
| Change every 1500 hours/ 12 months               |  | I .                 |
| USE  |  | CLIMATE             |
| Initial service                                  |  | Moderate            |

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Change every 500 hours

## ATLAS GMBH WHEELED LOADERS 4WD 42E DEUTZ F3L-1011F (1994-1998)



| HUB REDUCTIONS FRONT               |      |                     |  |
|------------------------------------|------|---------------------|--|
| USE                                |      | CLIMATE             |  |
| Normal                             |      | Moderate            |  |
| PRODUCT RECOMMENDATION 1           |      |                     |  |
| Gearlube LS 80W-90                 |      |                     |  |
| Change every 1500 hours/ 12 months |      |                     |  |
| USE                                |      | CLIMATE             |  |
| Initial service                    |      | Moderate            |  |
| PRODUCT RECOMMENDATION 1           |      |                     |  |
| Gearlube LS 80W-90                 |      |                     |  |
| Change every 500 hours             |      |                     |  |
|                                    |      |                     |  |
| HUB REDUCTIONS REAR                |      |                     |  |
| USE                                |      | CLIMATE             |  |
| Normal                             |      | Moderate            |  |
| PRODUCT RECOMMENDATION 1           |      |                     |  |
| Gearlube LS 80W-90                 |      |                     |  |
| Change every 1500 hours/ 12 months |      |                     |  |
| USE                                |      | CLIMATE             |  |
| Initial service                    |      | Moderate            |  |
| PRODUCT RECOMMENDATION 1           |      |                     |  |
| Gearlube LS 80W-90                 |      |                     |  |
| Change every 500 hours             |      |                     |  |
|                                    |      |                     |  |
| HYDRAULIC SYSTEM HYDROSTATIC D     | RIVE |                     |  |
| use<br>Normal                      |      | CLIMATE<br>Moderate |  |
| PRODUCT RECOMMENDATION 1           |      | Widuelate           |  |
| Perlus H 46                        |      |                     |  |
| Change every 12 months             |      |                     |  |
| USE                                |      | CLIMATE             |  |
| Initial service                    |      | Moderate            |  |
| PRODUCT RECOMMENDATION 1           |      |                     |  |
| Perlus H 46                        |      |                     |  |
| Change every 1500 hours            |      |                     |  |
|                                    |      |                     |  |

## **ATLAS GMBH WHEELED LOADERS 4WD 42E DEUTZ F3L-1011F** (1994-1998)



| HYDRAULIC BRAKE SYSTEM             |  |            |  |  |
|------------------------------------|--|------------|--|--|
| USE                                |  | CLIMATE    |  |  |
| Normal                             |  | Moderate   |  |  |
|                                    |  | iviouerate |  |  |
| PRODUCT RECOMMENDATION 1           |  |            |  |  |
| ATF Dexron II-D                    |  |            |  |  |
| Change every 1500 hours/ 12 months |  |            |  |  |
| USE                                |  | CLIMATE    |  |  |
| Initial service                    |  | Moderate   |  |  |
| PRODUCT RECOMMENDATION 1           |  |            |  |  |
| ATF Dexron II-D                    |  |            |  |  |
| Change every 500 hours             |  |            |  |  |
|                                    |  |            |  |  |
| GREASE POINTS/NIPPLES              |  |            |  |  |
| USE                                |  | CLIMATE    |  |  |
| Normal                             |  | Moderate   |  |  |
| PRODUCT RECOMMENDATION 1           |  |            |  |  |
| MoS2 Grease EP 2                   |  |            |  |  |
|                                    |  |            |  |  |
|                                    |  |            |  |  |
| ANTI-FRICTION BEARINGS             |  |            |  |  |
| USE                                |  | CLIMATE    |  |  |
| Normal                             |  | Moderate   |  |  |
| PRODUCT RECOMMENDATION 1           |  |            |  |  |
| MoS2 Grease EP 2                   |  |            |  |  |
|                                    |  |            |  |  |
| PLAIN BEARINGS                     |  |            |  |  |
| USE                                |  | CLIMATE    |  |  |
| Normal                             |  | Moderate   |  |  |
|                                    |  |            |  |  |
| PRODUCT RECOMMENDATION 1           |  |            |  |  |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

MoS2 Grease EP 2