ATLAS WEYHAUSEN (WEYCOR) WHEELED LOADERS AR AR45 DEUTZ F3L-1011F (1999-



2002)

ENGINE Deutz USE Normal PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Armado Synth 10W-40 Change every 250 hours/ 3 months USE Initial service PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Armado Synth 10W-40 PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Armado Synth 10W-40 Change every 50 hours DIFFERENTIAL USE			
Normal PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Armado Synth 10W-40 Change every 250 hours/ 3 months USE USE Initial Service PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Armado Synth 10W-40 Change every 50 hours DIFFERENTIAL USE Normal PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Change every 50 hours CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90 Change every 1500 hours/ 12 months USE CLIMATE	ENGINE Deutz		
PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Change every 250 hours/ 3 months USE Initial Service PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Change every 50 hours DIFFERENTIAL USE Normal PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Change every 50 hours CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate PRODUCT RECOMMENDATION 2 Armado Synth 10W-40 Change every 50 hours CLIMATE Moderate PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90 Change every 1500 hours/ 12 months USE CLIMATE	USE		CLIMATE
Agrisynth LSP 10W-40 Change every 250 hours/ 3 months USE Initial service PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Change every 50 hours DIFFERENTIAL USE Normal PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90 Change every 1500 hours/ 12 months USE CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate	Normal		Moderate
Change every 250 hours/ 3 months USE Initial service PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Change every 50 hours DIFFERENTIAL USE Normal PRODUCT RECOMMENDATION 2 Armado Synth 10W-40 CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90 Change every 1500 hours/ 12 months USE CLIMATE CLIMATE Moderate	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
USE Initial service PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Change every 50 hours DIFFERENTIAL USE Normal PRODUCT RECOMMENDATION 2 Armado Synth 10W-40 CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90 Change every 1500 hours/ 12 months USE CLIMATE CLIMATE Moderate	Agrisynth LSP 10W-40	Armado Synth 10W-40	
Initial service PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Armado Synth 10W-40 Change every 50 hours DIFFERENTIAL USE Normal PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90 Change every 1500 hours/ 12 months USE CLIMATE CLIMATE Moderate CLIMATE Moderate CLIMATE CLIMATE Moderate CLIMATE	Change every 250 hours/ 3 months		
PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Change every 50 hours DIFFERENTIAL USE Normal PRODUCT RECOMMENDATION 2 CLIMATE Moderate PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90 Change every 1500 hours/ 12 months USE CLIMATE CLIMATE Moderate	USE		CLIMATE
Agrisynth LSP 10W-40 Change every 50 hours DIFFERENTIAL USE Normal PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90 Change every 1500 hours/ 12 months USE CLIMATE Moderate CLIMATE LIMATE CLIMATE CLIMATE	Initial service		Moderate
Change every 50 hours DIFFERENTIAL USE Normal PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90 Change every 1500 hours/ 12 months USE CLIMATE Moderate CLIMATE CLIMATE CLIMATE	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
DIFFERENTIAL USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90 Change every 1500 hours/ 12 months USE CLIMATE	Agrisynth LSP 10W-40	Armado Synth 10W-40	
Normal Moderate PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90 Change every 1500 hours/ 12 months USE CLIMATE Moderate Moderate CLIMATE	Change every 50 hours		
Normal Moderate PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90 Change every 1500 hours/ 12 months USE CLIMATE Moderate Moderate CLIMATE			
Normal PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90 Change every 1500 hours/ 12 months USE CLIMATE	DIFFERENTIAL		
PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90 Change every 1500 hours/ 12 months USE CLIMATE	USE		CLIMATE
Gearlube LS 80W-90 Change every 1500 hours/ 12 months USE CLIMATE	Normal		Moderate
Change every 1500 hours/ 12 months USE CLIMATE	PRODUCT RECOMMENDATION 1		
USE CLIMATE	Gearlube LS 80W-90		
	Change every 1500 hours/ 12 months		
Initial service Moderate	USE		CLIMATE
initial service Woderate	Initial service		Moderate

CLIMATE
Moderate

Change every 1500 hours/ 12 months

Gearlube LS 80W-90

Change every 500 hours

USE	CLIMATE	
Initial service	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 500 hours		

ATLAS WEYHAUSEN (WEYCOR) WHEELED LOADERS AR AR45 DEUTZ F3L-1011F (1999-



2002)

HYDRAULIC SYSTEM	
USE	CLIMATE
Normal	Moderate
	Moderate
PRODUCT RECOMMENDATION 1 Perlus H 46	
Change every 12 months	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 1500 hours	
HYDROSTATIC DRIVE	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 12 months	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 1500 hours	
GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
	!

PRODUCT RECOMMENDATION

ATLAS WEYHAUSEN (WEYCOR) WHEELED LOADERS AR AR45 DEUTZ F3L-1011F (1999-



2002)

BRAKE SYSTEM RESERVOIR	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 1500 hours/ 12 months	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 500 hours	
PLAIN BEARINGS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

ROLLING CONTACT BEARINGS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.