ATLAS WEYHAUSEN (WEYCOR) WHEELED LOADERS AR AR95 SUPER DEUTZ TCD 2012 L04 (2011-2016)



ENGINE Deutz TCD 2012 L04 2V Capacity: 11 liter		
USE		CLIMATE
Normal, fuel sulfur level <0,5 %, amb	oient temperature > -10°C	Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 8 hours, change every 12 months/ 500 hours

DIFFERENTIAL FRONT Capacity: 7,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 500 hours, change every 12 i	months/ 1500 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 500 hours		

Change every 500 hours	
DIFFERENTIAL REAR Capacity: 7,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 500 hours, change every 12 i	onths/ 1500 hours
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 500 hours	

ATLAS WEYHAUSEN (WEYCOR) WHEELED LOADERS AR AR95 SUPER DEUTZ TCD 2012 L04 (2011-2016)



		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 500 hours, change every 12	? months/ 1500 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 500 hours		
HUB REDUCTIONS REAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90		
	? months/ 1500 hours	
Gearlube LS 80W-90	? months/ 1500 hours	CLIMATE
Gearlube LS 80W-90 Check every 500 hours, change every 12	? months/ 1500 hours	CLIMATE Moderate
Gearlube LS 80W-90 Check every 500 hours, change every 12 USE	? months/ 1500 hours	
Gearlube LS 80W-90 Check every 500 hours, change every 12 use Initial service	? months/ 1500 hours	

Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 500 hours, change every 12 i	months/ 1500 hours	
USE		CLIMATE
use Initial service		CLIMATE Moderate

KROON-OIL B.V. Postbus 149 7600 AC Almelo

Change every 500 hours

TRANSMISSION
Capacity: 1,8 liter

HYDRAULIC SYSTEM

ATLAS WEYHAUSEN (WEYCOR) WHEELED LOADERS AR AR95 SUPER DEUTZ TCD 2012 L04 (2011-2016)



USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	
Check every 8 hours, change every	/ 24 months/ 3000 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	
Change every 1500 hours		
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Check every 8 hours, change every	/ 24 months/ 3000 hours	
USE		CLIMATE
Fluid analysis		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	
Change every 1000 hours	·	·
GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM Capacity: 15 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Check every 8 hours, change every	24 months	·

PRODUCT RECOMMENDATION

ATLAS WEYHAUSEN (WEYCOR) WHEELED LOADERS AR AR95 SUPER DEUTZ TCD 2012 L04 (2011-2016)



BRAKE SYSTEM RESERVOIR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 500 hours, change every 12 i	months/ 1500 hours	
USE		CLIMATE
Initial service		Moderate
Initial service PRODUCT RECOMMENDATION 1		Moderate
		Moderate

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.