PRODUCT RECOMMENDATION

# ATLET COUNTERBALANCE FORKLIFT TRUCKS, DIESEL DG/DH/DL DG-50 (2005 AND AFTER)

## ENGINE Nissan TD42

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Dieselfleet CD+ 15W-40** | **Multifleet SHPD 15W-40** | **Multifleet SCD 30** |

*Check every 10 hours, change every 500 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Kroontrak MTH 10W-30** | **Synfleet SHPD 10W-40** | **Multifleet SHPD 10W-40** |

*Check every 10 hours, change every 500 hours*

## DIFFERENTIAL FRONT

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | | |
| **Gearlube GL-5 85W-140** | | |

*Change every 12 months/ 2400 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Cold |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Change every 12 months/ 2400 hours*

## TRANSMISSION AUTOMATIC

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **ATF Dexron II-D** | **ATF-F (Ford)** | |

*Change every 6 months/ 1200 hours*

## HYDRAULIC SYSTEM

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Perlus H 32** | | |

*Change every 12 months/ 2400 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# ATLET COUNTERBALANCE FORKLIFT TRUCKS, DIESEL DG/DH/DL DG-50 (2005 AND AFTER)

## HYDRAULIC BRAKE SYSTEM

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Drauliquid DOT 3** | | |

*Change every 12 months/ 2400 hours*

## GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Gear Grease EP 1** | | |

*Change every 3 months/ 600 hours*

## GREASE POINTS/NIPPLES WHEEL BEARINGS

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

*Change every 12 months/ 2400 hours*

## COOLING SYSTEM

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Coolant -38 Organic NF** | **Coolant -26** | |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367