## ATLET COUNTERBALANCE FORKLIFT TRUCKS, DIESEL DG/DH/DL DG-60 (2005 AND AFTER)



**Multifleet SHPD 10W-40** 

ENGINE Nissan TD42		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30
Check every 10 hours, change every 500 h	nours	
USE		CLIMATE

10W-40

Norr PROD

		CLIMATE
mal		Moderate
DUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

Kroontrak MTH 10W-30 Synfle	leet SHPD
-----------------------------	-----------

Check every 10 hours, change every 500 hours

DIFFERENTIAL FRONT	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 85W-140	
Change every 12 months/ 2400 hours	
USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 2

Change ever	y 12 months/	2400 hours
-------------	--------------	------------

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

TRANSMISSION AUTOMATIC		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	ATF-F (Ford)	

Unigear HS GL-3/GL-5 80W-90

Change every 6 months/ 1200 hours

HYDRAULIC SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	
Change every 12 months/ 2400 hours	

## ATLET COUNTERBALANCE FORKLIFT TRUCKS, DIESEL DG/DH/DL DG-60 (2005 AND AFTER)



HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
0 h = 1 = 1 = 1 = 1 = 1 = 1 = 1 = 1 = 1 =	

Change every 12 months/ 2400 hours

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Grease EP 1	
Change every 3 months/ 600 hours	

GREASE POINTS/NIPPLES WHEEL BEARINGS
USE
CLIMATE

Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 12 months/ 2400 hours

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE
COOLING SYSTEM		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.