## ATLET COUNTERBALANCE FORKLIFT TRUCKS, ELECTRIC EF/EH/ET EH-20 (2005



AND AFTER)

DIFFERENTIAL FRONT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Change every 12 months/ 2400 ho	ure	

Change every 12 months/ 2400 hours

REDUCTION GEARS		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
Change every 12 months/ 2400 hours		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W
Change every 12 months/ 2400 hours		1

HYDRAULIC SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	
Change every 6 months/ 1200 hours	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Perlus H 15	
Change every 6 months/ 1200 hours	

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Change every 12 months/ 2400 hours		·

PRODUCT RECOMMENDATION

## ATLET COUNTERBALANCE FORKLIFT TRUCKS, ELECTRIC EF/EH/ET EH-20 (2005



AND A	FTER)
-------	-------

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Grease EP 1	
Change every 3 months/ 600 hours	

GREASE POINTS/NIPPLES WHEEL BEARINGS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change avenue 12 months / 2400 ha		

Change every 12 months/ 2400 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.