ATLET COUNTERBALANCE FORKLIFT TRUCKS, LPG GG/GH/GL GH-40 NISSAN



TB45 (2007 AND AFTER)

ENGINE Nissan TB45		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HDX 20W-50	Multifleet SHPD 20W-50	
Check every 10 hours, change every 500	hours	•
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	
Check every 10 hours, change every 500	hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Check every 10 hours, change every 500	hours	

DIFFERENTIAL FRONT		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
Change every 12 months/ 2400 hours		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 12 months/ 2400 hours		

TRANSMISSION AUTOMATIC		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	ATF-F (Ford)	
Change every 6 months/ 1200 hou	rs	'

KROON-OIL B.V. Postbus 149 7600 AC Almelo

ATLET COUNTERBALANCE FORKLIFT TRUCKS, LPG GG/GH/GL GH-40 NISSAN TB45 (2007 AND AFTER)



HYDRAULIC SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	
Change every 12 months/ 2400 hours	

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Change every 12 months/ 2400 hours	

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Grease EP 1	
Change every 3 months/ 600 hours	·

GREASE POINTS/NIPPLES WHEEL BEARINGS			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
Change every 12 months/ 2400 ho	urs		

COOLING SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.