## AUSA WHEELED DUMPERS 300 RH ISUZU 3LD1 (1994-2005)



<b>ENGINE</b> Isuzu 3LD1 Capacity: 6,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30
Change every 250 hours/ 6 months		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Change every 250 hours/ 6 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30
Change every 50 hours		
USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Change every 50 hours		
GEARBOX DIFFERENTIAL REDUCTOR Capacity: 2 liter	UNIT	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coorlybal S 90W 00		

Gearlube LS 80W-90

Change every 1000 hours

USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 50 hours	·

## AUSA WHEELED DUMPERS 300 RH ISUZU 3LD1 (1994-2005)



HYDRAULIC SYSTEM Capacity: 30 liter (Hydraulic tank)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	

Change every 1000 hours

HYDRAULIC BRAKE SYSTEM Capacity: 0,25 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	
Change every 1000 hours	

## **ARTICULATION JOINTS**

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

COOLING SYSTEM Capacity: 5,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Change even 750 hours	·	·	

Change every 750 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.