
AUSA WHEELED DUMPERS 350 AHG ISUZU

(1996-2005)



Capacity: 7,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1 Dieselfleet CD+ 15W-40	PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40	PRODUCT RECOMMENDATION 3 Multifleet SCD 30
	Widitilieet SHFD 13W-40	Multifleet 3CD 30
Change every 200 hours		
Normal		CLIMATE Cold
PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20		
Change every 200 hours	,	
use Initial service		сымате Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30
Change every 50 hours		
USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Change every 50 hours		
DIFFERENTIAL FRONT Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 1000 hours		
use Initial service		climate Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 50 hours	·	

AUSA WHEELED DUMPERS 350 AHG ISUZU





DIFFERENTIAL REAR Capacity: 2,25 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 1000 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 50 hours	
HUB REDUCTIONS Capacity: 0,25 liter (each hub)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 1000 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 50 hours	
HYDRAULIC SYSTEM Capacity: 50 liter (Hydraulic tank)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 1000 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 100 hours	

AUSA WHEELED DUMPERS 350 AHG ISUZU



(1996-2005)

HYDRAULIC ACTUATION OIL IMMERSED BRAKES				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Multifleet SCD 10W	HDX 10W			
Change every 1000 hours				

ARTICULATION JOINTS

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		
Change every 50 hours	1			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.