## AVELING BARFORD ARTICULATED DUMP TRUCKS RXD-24 6X6



ENGINE Cummins LT10-225		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

DIFFERENTIAL LIMITED SLIP AXLE 1		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 800 hours/ 12 months		

DIFFERENTIAL LIMITED SLIP AXLE 2		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 800 hours/ 12 months	·	

DIFFERENTIAL LIMITED SLIP AXLE 3		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 800 hours/ 12 months		

HUB REDUCTIONS AXLE 1			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Gearlube LS 80W-90			

Change every 800 hours/ 12 months

## AVELING BARFORD ARTICULATED DUMP TRUCKS RXD-24 6X6



HUB REDUCTIONS AXLE 2		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 800 hours/ 12 months

HUB REDUCTIONS AXLE 3		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change avery 800 hours/ 12 months		

Change every 800 hours/ 12 months

TRANSMISSION ZF 6WG200	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Multifleet SCD 20W-20	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	

HYDRAULIC SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	
Change every 1200 hours/ 12 months	•

CENTRAL LUBRICATION SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Gear Grease EP 00/000			

## AVELING BARFORD ARTICULATED DUMP TRUCKS RXD-24 6X6



## GREASE POINTS/NIPPLES use CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Labora Grease Q5 MP Calcep Grease EP 2 MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.