## BARFORD SITE DUMPERS SK10 (2008 AND AFTER)



| ENGINE Iveco N45 MNTD      |                          |                               |
|----------------------------|--------------------------|-------------------------------|
| USE                        |                          | CLIMATE                       |
| Normal                     |                          | Mediterranean                 |
| PRODUCT RECOMMENDATION 1   |                          |                               |
| Agridiesel CRD+ 15W-40     |                          |                               |
| Change every 500 hours     |                          |                               |
| USE                        |                          | CLIMATE                       |
| Normal                     |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| Agrisynth LSP Ultra 10W-40 | Agrisynth LSP 10W-40     | Armado Synth LSP Ultra 10W-40 |
| Change every 500 hours     |                          |                               |
| USE                        |                          | CLIMATE                       |
| Initial service            |                          | Mediterranean                 |
| PRODUCT RECOMMENDATION 1   |                          |                               |
| Agridiesel CRD+ 15W-40     |                          |                               |
| Change every 50 hours      |                          | ·                             |

| Initial service            |                          | Moderate                      |
|----------------------------|--------------------------|-------------------------------|
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| Agrisynth LSP Ultra 10W-40 | Agrisynth LSP 10W-40     | Armado Synth LSP Ultra 10W-40 |
| Change every 50 hours      |                          |                               |
|                            |                          |                               |
| DIFFERENTIAL FRONT         |                          |                               |

CLIMATE

| DIFFERENTIAL FRONT       |                             |          |
|--------------------------|-----------------------------|----------|
| USE                      |                             | CLIMATE  |
| Normal                   |                             | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90     | Unigear HS GL-3/GL-5 80W-90 |          |
| Change every 1000 hours  |                             |          |

| USE                      |                             | CLIMATE  |
|--------------------------|-----------------------------|----------|
| Normal                   |                             | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90     | Unigear HS GL-3/GL-5 80W-90 |          |
| Change every 1000 hours  |                             |          |

## BARFORD SITE DUMPERS SK10 (2008 AND AFTER)



| HUB REDUCTIONS FRONT     |                             |          |
|--------------------------|-----------------------------|----------|
| USE                      |                             | CLIMATE  |
| Normal                   |                             | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90     | Unigear HS GL-3/GL-5 80W-90 |          |
| Change every 1000 hours  | ,                           | •        |

| HUB REDUCTIONS REAR      |                             |          |  |
|--------------------------|-----------------------------|----------|--|
| USE                      |                             | CLIMATE  |  |
| Normal                   |                             | Moderate |  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    |          |  |
| Gearlube GL-5 80W-90     | Unigear HS GL-3/GL-5 80W-90 |          |  |

Change every 1000 hours

| TRANSFERBOX              |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| ATF-F (Ford)             |          |
| Change every 1000 hours  |          |

| TRANSMISSION PowerShuttle/ITL |          |
|-------------------------------|----------|
| USE                           | CLIMATE  |
| Normal                        | Moderate |
| PRODUCT RECOMMENDATION 1      |          |
| ATF-F (Ford)                  |          |
| Change every 1000 hours       | ·        |

| HYDRAULIC SYSTEM Capacity: 40 liter |                          |          |  |
|-------------------------------------|--------------------------|----------|--|
| USE                                 |                          | CLIMATE  |  |
| Normal                              |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2 |          |  |
| Perlus H 32                         | Perlus AF 32             |          |  |
| Change every 1000 hours             | '                        | '        |  |

## BARFORD SITE DUMPERS SK10 (2008 AND AFTER)



| HYDRAULIC BRAKE SYSTEM   |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| Perlus H 15              |          |

| GREASE POINTS/NIPPLES    |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

| COOLING SYSTEM           |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| Coolant -38 Organic NF   |          |
| Change every 1000 hours  | ·        |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.