

# BARFORD SITE DUMPERS SX6000 IVECO

## 8045E00.50A N/A (2001-2003)


**ENGINE** Iveco 8045.E00.50A N/A

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40***Change every 300 hours*
**DIFFERENTIAL FRONT**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 600 hours*
**DIFFERENTIAL REAR**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 600 hours*
**HUB REDUCTIONS FRONT**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 600 hours*
**HUB REDUCTIONS REAR**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 600 hours*
**TRANSFERBOX O & S**

We are unable to give a standard recommendation for this component. Please contact our service department.

# BARFORD SITE DUMPERS SX6000 IVECO

## 8045E00.50A N/A (2001-2003)



### TRANSMISSION PowerShuttle/ITL

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF-F (Ford)</b>		

*Change every 1200 hours/ 12 months*

### HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

*Change every 1200 hours/ 12 months*

### HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*