BARFORD SITE DUMPERS SX9000 IVECO 8045E00.50A T/C (TILL 2003)



ENGINE Iveco 8045.E00.50A T/C		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
01 0001		

Change every 300 hours

DIFFERENTIAL FRONT	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 600 hours	·

DIFFERENTIAL REAR	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 600 hours	·

HUB REDUCTIONS FRONT	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 600 hours	

HUB REDUCTIONS REAR	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 600 hours	·

TRANSFERBOX 0 & S

We are unable to give a standard recommendation for this component. Please contact our service department.

BARFORD SITE DUMPERS SX9000 IVECO 8045E00.50A T/C (TILL 2003)



TRANSMISSION PowerShuttle/ITL		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF-F (Ford)		
Change every 1200 hours/ 12 months		

HYDRAULIC SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	
Change every 1200 hours/ 12 months	·

HYDRAULIC BRAKE SYSTEM

USE CLIMATE

Normal Moderate

PRODUCT RECOMMENDATION 1

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Perlus H 32