PRODUCT RECOMMENDATION

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B40CM MKII (6X6) MERCEDES-BENZ OM442LA

ENGINE Mercedes-Benz OM442LA
Capacity: 28 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel CRD+ 15W-40	**Synfleet SHPD 10W-40**	**Armado Synth 5W-30**

Change every 250 hours/ 6 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel CRD+ 15W-40	**Synfleet SHPD 10W-40**	**Armado Synth 5W-30**

Change every 100 hours

DRIVE AXLES Bell
Capacity: 45 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 85W-140	**Unigear LS GL-3/GL-5 85W-140**	

Check every 250 hours, change every 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 250 hours, change every 2000 hours

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 85W-140	**Unigear LS GL-3/GL-5 85W-140**	

Change every 100 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 100 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B40CM MKII (6X6) MERCEDES-BENZ OM442LA

TRANSFERBOX
Capacity: 8,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Check every 250 hours, change every 2000 hours

TRANSMISSION Allison HD4560R
Capacity: 48 liter (Initial fill with retarder), Capacity: 44 liter (Initial fill without retarder)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Change every 1000 hours

HYDRAULIC SYSTEM
Capacity: 140 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	**Multifleet SCD 10W**	

Change every 2000 hours

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Change every 2000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	**Labora Grease**	

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B40CM MKII (6X6) MERCEDES-BENZ OM442LA

COOLING SYSTEM
Capacity: 50 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	**Coolant SP 12**	
Change every 2000 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367