

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B40D MK II (6X6)

MERCEDES-BENZ OM501LA (TIER 2)



ENGINE Mercedes-Benz OM501LA
Capacity: 32 liter (Dry fill), Capacity: 30 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2

Armado Synth 10W-40

Change every 500 hours

DIFFERENTIAL FRONT Bell 25T
Capacity: 46 liter (Dry fill), Capacity: 45 liter (Service fill)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140

Check every 1000 hours, change every 2000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Check every 1000 hours, change every 2000 hours

DIFFERENTIAL FRONT (WET DISC BRAKES) Bell
Capacity: 110 liter (Dry fill), Capacity: 45,3 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 3

Agrifluid HT-Plus

Change every 1000 hours

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B40D MK II (6X6) MERCEDES-BENZ OM501LA (TIER 2)

**DIFFERENTIAL MIDDLE** Bell 25T

Capacity: 46 liter (Dry fill), Capacity: 45 liter (Service fill)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Check every 1000 hours, change every 2000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 1000 hours, change every 2000 hours***DIFFERENTIAL MIDDLE (WET DISC BRAKES)** Bell

Capacity: 110 liter (Dry fill), Capacity: 45,3 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-20

PRODUCT RECOMMENDATION 2

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 3

Agrifluid HT-Plus*Change every 1000 hours***DIFFERENTIAL REAR** Bell 25T

Capacity: 46 liter (Dry fill), Capacity: 45 liter (Service fill)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Check every 1000 hours, change every 2000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 1000 hours, change every 2000 hours*

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B40D MK II (6X6) MERCEDES-BENZ OM501LA (TIER 2)



DIFFERENTIAL REAR (WET DISC BRAKES) Bell
Capacity: 110 liter (Dry fill), Capacity: 45,3 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Change every 1000 hours

FINAL DRIVES
Capacity: 6,3 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Check every 1000 hours, change every 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 1000 hours, change every 2000 hours

TRANSFERBOX VGR 17000
Capacity: 4,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Change every 2000 hours

TRANSMISSION Allison HD4560R
Capacity: 40 liter (Dry fill), Capacity: 34 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Check every 500 hours, change every 2000 hours

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B40D MK II (6X6) MERCEDES-BENZ OM501LA (TIER 2)

**HYDRAULIC SYSTEM**

Capacity: 185 liter (Hydraulic system including tank), Capacity: 177,6 liter (Hydraulic tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Multifleet SCD 10W	

Change every 4000 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 33,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.