## BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B50D MK VI (2008



AND AFTER)

<b>ENGINE</b> Mercedes-Benz OM502LA Capacity: 30 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth LSP 10W-40	Armado Synth 10W-40	

Check every 10 hours, change every 500 hours

<b>DIFFERENTIAL FRONT</b> Bell 25T Capacity: 50 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid Synth XHP Ultra	
Change every 2000 hours	

<b>DIFFERENTIAL REAR</b> Bell 25T Capacity: 50 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid Synth XHP Ultra	
Change every 2000 hours	'

HUB REDUCTIONS FRONT Capacity: 6,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid Synth XHP Ultra	
Change every 2000 hours	·

HUB REDUCTIONS REAR Capacity: 6,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid Synth XHP Ultra	
Change every 2000 hours	·

Dollegoorweg 15

7602 EC Almelo

## **BELL EQUIPMENT ARTICULATED DUMP** TRUCKS B-C-D-E SERIES B50D MK VI (2008



AND AFTER)

TRANSFERBOX Capacity: 4,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	
Change every 2000 hours	

**TRANSMISSION** Capacity: 34 liter CLIMATE Normal Moderate

PRODUCT RECOMMENDATION 1 SP Matic 2032

Change every 2000 hours

HYDRAULIC SYSTEM Capacity: 256 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF-F (Ford)	
Change every 4000 hours	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 50 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Change every 2000 hours		·

PRODUCT RECOMMENDATION

## BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B50D MK VI (2008



AND AFTER)

COOLING SYSTEM WET BRAKES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Change every 2000 hours	-	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.