

# BOBCAT SKID STEER LOADERS 853 (1991-1996)



**ENGINE** Isuzu 4JB1 PK-03  
Capacity: 7,6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Tropical |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |  |
|-------------------------------|--------------------------|--|
| <b>Multifleet SHPD 20W-50</b> | <b>Multifleet SCD 40</b> |  |

*Check every 10 hours, change every 250 hours*

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Multifleet SCD 30</b> |  |  |

*Check every 10 hours, change every 250 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3      |
|-----------------------------|-----------------------------|-------------------------------|
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

*Check every 10 hours, change every 250 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Multifleet SCD 10W</b> |  |  |

*Check every 10 hours, change every 250 hours*

## HYDRAULIC SYSTEM HYDROSTATIC DRIVE

Capacity: 14,7 liter (Hydraulic tank), Capacity: 30,3 liter (System)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
|-----------------------------|--------------------------|-------------------------------|
| <b>Kroontrak MTH 10W-30</b> | <b>Asyntho 5W-30</b>     | <b>Multifleet SHPD 10W-40</b> |

*Check every 50 hours, change every 1000 hours/ 12 months*

## GREASE POINTS/NIPPLES

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
|--------------------------|---------------------------------|------------------------------|
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

*Check every 10 hours*

# BOBCAT SKID STEER LOADERS 853 (1991-1996)



## COOLING SYSTEM

Capacity: 20,8 liter

| USE                           |                          | CLIMATE                  |
|-------------------------------|--------------------------|--------------------------|
| Normal                        |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       | <b>Coolant -33 MPG</b>   |

Check every 10 hours

## CHAIN CASE

Capacity: 34,1 liter (Reservoir)

| USE                         |                          | CLIMATE                       |
|-----------------------------|--------------------------|-------------------------------|
| Normal                      |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Kroontrak MTH 10W-30</b> | <b>Asyntho 5W-30</b>     | <b>Multifleet SHPD 10W-40</b> |

Check every 50 hours, change every 1000 hours/ 12 months

## HYDRAULIC FAN GEARBOX

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

Check every 250 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.