

# BOBCAT TELESCOPIC HANDLERS T2566

## PERKINS 1004.40T (2000-2004)



**ENGINE** Perkins 1004.40T  
Capacity: 6,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1  
**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2  
**Multifleet SHPD 15W-40**

*Check every 10 hours, change every 600 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1  
**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2  
**Multifleet SHPD 15W-40**

*Change every 100 hours*

**DIFFERENTIAL FRONT**  
Capacity: 10,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1  
**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2  
**Agrifluid Synth XHP Ultra**

PRODUCT RECOMMENDATION 3  
**Agrifluid HT-Plus**

*Check every 100 hours, change every 600 hours*

**DIFFERENTIAL REAR**  
Capacity: 10 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1  
**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2  
**Agrifluid Synth XHP Ultra**

PRODUCT RECOMMENDATION 3  
**Agrifluid HT-Plus**

*Check every 100 hours, change every 600 hours*

**HUB REDUCTIONS FRONT**  
Capacity: 0,7 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1  
**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2  
**Agrifluid Synth XHP Ultra**

PRODUCT RECOMMENDATION 3  
**Agrifluid HT-Plus**

*Check every 100 hours, change every 600 hours*

# BOBCAT TELESCOPIC HANDLERS T2566

## PERKINS 1004.40T (2000-2004)

**HUB REDUCTIONS REAR**

Capacity: 0,7 liter

| USE                         |                                  | CLIMATE                  |
|-----------------------------|----------------------------------|--------------------------|
| Normal                      |                                  | Moderate                 |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2         | PRODUCT RECOMMENDATION 3 |
| <b>Kroontrak CVT 10W-40</b> | <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> |

Check every 100 hours, change every 600 hours

**TRANSFERBOX**

| USE                         |                                  | CLIMATE                  |
|-----------------------------|----------------------------------|--------------------------|
| Normal                      |                                  | Moderate                 |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2         | PRODUCT RECOMMENDATION 3 |
| <b>Kroontrak CVT 10W-40</b> | <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> |

**HYDRAULIC SYSTEM**

Capacity: 70 liter

| USE                       |                          | CLIMATE  |
|---------------------------|--------------------------|----------|
| Normal                    |                          | Moderate |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus Biosynth 46</b> | <b>Perlus H 46</b>       |          |

Check every 100 hours, change every 600 hours

**HYDRAULIC BRAKE SYSTEM**

Capacity: 0,4 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>LHM +</b>             |  |          |

Check every 100 hours, change every 600 hours

**COOLING SYSTEM**

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.