PRODUCT RECOMMENDATION

BOBCAT UTILITY VEHICLES 2200D
KUBOTA D722

ENGINE Kubota D722
Capacity: 2,8 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		

Check every 10 hours, change every 100 hours/ 12 months

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Check every 10 hours, change every 100 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	**Kroontrak MTH 10W-30**	**Asyntho 5W-30**

Check every 10 hours, change every 100 hours/ 12 months

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Check every 10 hours, change every 100 hours/ 12 months

USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		

Check every 10 hours, change every 50 hours

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Check every 10 hours, change every 50 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	**Kroontrak MTH 10W-30**	**Asyntho 5W-30**

Check every 10 hours, change every 50 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

BOBCAT UTILITY VEHICLES 2200D
KUBOTA D722

USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Check every 10 hours, change every 50 hours

DIFFERENTIAL FRONT
Capacity: 0,15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agrifluid Synth XHP Ultra	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

Check every 1 months, change every 12 months/ 100 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agrifluid Synth XHP Ultra	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

Check every 1 months, change every 12 months/ 50 hours

DIFFERENTIAL REAR
Capacity: 0,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agrifluid Synth XHP Ultra	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

Check every 1 months, change every 12 months/ 300 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agrifluid Synth XHP Ultra	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

Check every 1 months, change every 12 months/ 50 hours

HYDRAULIC BRAKE SYSTEM
Capacity: 0,25 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

BOBCAT UTILITY VEHICLES 2200D
KUBOTA D722

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Change every 1 months

COOLING SYSTEM
Capacity: 7,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Coolant -38 Organic NF	**Coolant -26**	

Check every 10 hours, change every 100 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367