

CASE MINI EXCAVATORS CK/CX CX28

PERKINS 103-13 (2002-2004)



ENGINE Perkins 103-13
Capacity: 5,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 250 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Asyntho 5W-30	Armado Synth 5W-30

Check every 10 hours, change every 250 hours

HYDRAULIC SYSTEM

Capacity: 46 liter (Hydraulic tank), Capacity: 60 liter (Total)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Check every 10 hours, change every 2000 hours

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 10 hours, change every 2000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

Change every 50 hours

CASE MINI EXCAVATORS CK/CX CX28

PERKINS 103-13 (2002-2004)



COOLING SYSTEM

Capacity: 5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 1000 hours

GEAR REDUCTION UNIT

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 2000 hours

SWING RING GEAR TEETH

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

Change every 250 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.