PRODUCT RECOMMENDATION

CASE SKID STEER LOADERS 1845B (1982-1985)

ENGINE Case 4-390

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Dieselfleet CD+ 15W-40	**Multifleet SHPD 15W-40**	

Change every 100 hours

HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Agrifluid Synth XHP Ultra	**Agrifluid HT-Plus**	

Change every 1000 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

DRIVE CHAIN COMPARTMENTS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HDX 30		

Change every 500 hours

GEAR REDUCTION UNIT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367