# CASE WHEELED EXCAVATORS WX WX210 SERIES 2 (2008-2018)



<b>ENGINE</b> Case 667TA/MEE Tier 3 Capacity: 16 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

### **DIFFERENTIAL FRONT**

Capacity: 11,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

#### **DIFFERENTIAL REAR**

Capacity: 12 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

### **HUB REDUCTIONS FRONT**

Capacity: 2,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

### **HUB REDUCTIONS REAR**

Capacity: 2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

### TRANSFERBOX (4x4)

Capacity: 2,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC SYSTEM Capacity: 160 liter (Hydraulic tank), Capacity: 285 liter (System)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Perlus H 68				

	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 12	Coolant -38 Organic NF

# CASE WHEELED EXCAVATORS WX WX210 SERIES 2 (2008-2018)



SWING REDUCTION UNIT Capacity: 4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.