## **CASE WHEELED LOADERS 221D PERKINS 704-30** (2002-2005)



| <b>ENGINE</b> Perkins 704.30 Capacity: 8,5 liter |                          |                          |
|--|--------------------------|--------------------------|
| USE  |                          | CLIMATE                  |
| Normal   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40                           | Dieselfleet CD+ 15W-40   | Multifleet SHPD 15W-40   |

Check every 10 hours, change every 500 hours/ 12 months

| <b>DIFFERENTIAL FRONT AND REAR</b> Capacity: 3,7 liter |          |
|--|----------|
| USE  | CLIMATE  |
| Normal   | Moderate |
| PRODUCT RECOMMENDATION 1                               |          |
| Gearlube LS 80W-90                                     |          |
| Change every 1000 hours/ 12 months                     | ·        |

| HUB REDUCTIONS Capacity: 0,5 liter |          |
|------------------------------------|----------|
| USE                                | CLIMATE  |
| Normal                             | Moderate |
| PRODUCT RECOMMENDATION 1           |          |
| Gearlube LS 80W-90                 |          |

Check every 500 hours, change every 1000 hours/ 12 months

| TRANSFERBOX (4x4) Capacity: 3,7 liter |          |
|---------------------------------------|----------|
| USE                                   | CLIMATE  |
| Normal                                | Moderate |
| PRODUCT RECOMMENDATION 1              |          |
| Gearlube LS 80W-90                    |          |
| Change every 1000 hours/ 12 months    | <u>'</u> |

| TRANSMISSION HYDROSTATIC Capacity: 0-0 liter (Combined with hydraulic system) |                          |          |
|---|--------------------------|----------|
| USE   |                          | CLIMATE  |
| Normal  |                          | Moderate |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |          |
| SP Matic 2032   | ATF Almirol              |          |
| Change every 36 months/ 3000 ho   | urs                      | ,        |

## **CASE WHEELED LOADERS 221D PERKINS 704-30** (2002-2005)



| HYDRAULIC SYSTEM Capacity: 40 liter (Hydraulic tank), Capacity: 65 liter (Total) |                          |          |
|--|--------------------------|----------|
| USE  |                          | CLIMATE  |
| Normal   |                          | Moderate |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2 |          |
| SP Matic 2032  | ATF Almirol              |          |
|  |                          |          |

Change every 36 months/ 3000 hours

| GREASE POINTS/NIPPLES    |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| MoS2 Grease EP 2         |          |
| Change every 50 hours    | ·        |

| COOLING SYSTEM Capacity: 15,5 liter |                          |          |
|-------------------------------------|--------------------------|----------|
| USE                                 |                          | CLIMATE  |
| Normal                              |                          | Moderate |
| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2 |          |
| Coolant -38 Organic NF              | Coolant -26              |          |
|                                     |                          |          |

Check every 10 hours, change every 2000 hours/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.