

CASE WHEELED LOADERS 421B PERKINS

1004-4T (1995-2001)



ENGINE Perkins 1004.T4
Capacity: 9,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40

Change every 250 hours

DIFFERENTIAL FRONT

Capacity: 3,85 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140

Change every 1000 hours

DIFFERENTIAL FRONT AND REAR

Capacity: 16 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140

Change every 1000 hours

DIFFERENTIAL REAR

Capacity: 3,85 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140

Change every 1000 hours

HUB REDUCTIONS

Capacity: 2,2 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140

Change every 1000 hours

CASE WHEELED LOADERS 421B PERKINS

1004-4T (1995-2001)



TRANSMISSION Powershift
Capacity: 17,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 10W-40

Change every 1000 hours

HYDRAULIC SYSTEM

Capacity: 65 liter (Hydraulic tank), Capacity: 80 liter (Total)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3

Agrifluid HT

Change every 2000 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Change every 24 months

COOLING SYSTEM

Capacity: 24 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26

Change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.