

CASE WHEELED LOADERS 521F FPT F4HFE413J STAGE 3B/TIER 4I (2012-2016)

**ENGINE** FPT F4HFE413J

Capacity: 11,8 liter, Filter capacity: 0,9 liter

| USE | | CLIMATE |
|-----------------------------------|-----------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP Ultra 10W-40 | Agrisynth MSP 10W-40 | Agridiesel MSP 15W-40 |

DIFFERENTIAL FRONT ZF MT-L3065-II

Capacity: 22 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR ZF MT-L3065-II

Capacity: 22 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION POWERSHIFT ZF 4WG130 4/3

Capacity: 18,9 liter (Change capacity), Capacity: 26 liter (Total)

| USE | | CLIMATE |
|----------------------------------|--------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Agrifluid HT |

HYDRAULIC SYSTEM

Capacity: 56,8 liter (Hydraulic tank), Capacity: 113,6 liter (System)

| USE | | CLIMATE |
|---------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus Biosynth 46 | Perlus H 46 | |

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| MoS2 Grease EP 2 | | |

CASE WHEELED LOADERS 521F FPT F4HFE413J STAGE 3B/TIER 4I (2012-2016)

**COOLING SYSTEM**

Capacity: 22 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.