

# CASE WHEELED LOADERS 621C CASE 6T-590 (1998-2003)



**ENGINE** Case 6T-590  
Capacity: 15,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Check every 10 hours, change every 250 hours*

**DIFFERENTIAL FRONT**  
Capacity: 8,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	

*Change every 1000 hours*

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	

*Change every 500 hours*

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	

*Change every 100 hours*

# CASE WHEELED LOADERS 621C CASE 6T-590 (1998-2003)



## DIFFERENTIAL REAR

Capacity: 8,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	

*Change every 1000 hours*

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	

*Change every 500 hours*

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	

*Change every 100 hours*

## HUB REDUCTIONS

Capacity: 5,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	

*Change every 1000 hours*

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	

*Change every 500 hours*

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	

*Change every 100 hours*

# CASE WHEELED LOADERS 621C CASE 6T-590 (1998-2003)



## TRANSMISSION POWERSHIFT ZF 4/3

Capacity: 7,6 liter (Change capacity), Capacity: 18,9 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	

*Check every 50 hours, change every 1000 hours*

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	

*Check every 50 hours, change every 100 hours*

## HYDRAULIC SYSTEM

Capacity: 90 liter (Hydraulic tank), Capacity: 153 liter (Total)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	

*Check every 50 hours, change every 2000 hours*

## COOLING SYSTEM

Capacity: 28 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 10 hours, change every 2000 hours/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.