## CASE WHEELED LOADERS 621D XR CASE 668TA/M2 (2003-2007)



ENGINE Case 668TA/M2 Capacity: 16,1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40		

Change every 500 hours

DIFFERENTIAL FRONT ZF Capacity: 20,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
01 100001	I	

Change every 1000 hours

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Change even 500 hours		

Change every 500 hours

DIFFERENTIAL REAR ZF Capacity: 20,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Change every 1000 hours

use Severe		сцмате Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Change aver E00 hours		

Change every 500 hours

## CASE WHEELED LOADERS 621D XR CASE 668TA/M2 (2003-2007)



HUB REDUCTIONS			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agrifluid HT-Plus	Agrifluid HT		
Change every 1000 hours			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agrifluid HT-Plus	Agrifluid HT		

Change every 500 hours

TRANSMISSION POWERSHIFT ZF 4/3 Capacity: 18,9 liter (Change capacity), Capacity: 26 liter (Dry fill)			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Agrifluid HT-Plus			
Change every 1000 hours			

HYDRAULIC SYSTEM Capacity: 68,5 liter (Hydraulic tank), Capacity: 113,6 liter (Total)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Agrifluid HT-Plus			
Change every 2000 hours			

COOLING SYSTEM Capacity: 34,1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Check every 10 hours, change ever	/ 2000 hours/ 24 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.