

CASE WHEELED LOADERS 921C CUMMINS

QSM11 (1999-2008)



ENGINE Cummins QSM11
Capacity: 36,9 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40

Change every 250 hours

DIFFERENTIAL FRONT
Capacity: 36,6 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR
Capacity: 36,3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS
Capacity: 13,6 liter (each hub)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION POWERSHIFT ZF 4/3
Capacity: 28,4 liter (Change capacity), Capacity: 46 liter (Dry fill)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

Check every 50 hours, change every 1000 hours

USE
First change only

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

Check every 50 hours, change every 100 hours

HYDRAULIC SYSTEM
Capacity: 125 liter (Hydraulic tank), Capacity: 242 liter (Total)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT-Plus

Check every 50 hours, change every 2000 hours

CASE WHEELED LOADERS 921C CUMMINS

QSM11 (1999-2008)

**COOLING SYSTEM**

Capacity: 57 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 2000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.