

ENGINE C15 Acert Capacity: 37,9 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Change every 250 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	
Change every 250 hours		·
USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 15W-40		
Change every 250 hours	-	
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40
Change every 250 hours		
TRANSMISSION Powershift Capacity: 155 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	

Check every 500 hours, change every 1000 hours

**Gear Oil Alcat 30** 

use Normal		climate Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 500 hours, change every 100	0 hours	•

**Gear Oil Alcat 50** 



HYDRAULIC SYSTEM Capacity: 75 liter (Tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 500 hours, change every 2000 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM Capacity: 76,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 17	
Change every 12000 hours/ 72 months	

BOGIE CARTRIDGE PINS

We are unable to give a standard recommendation for this component. Please contact our service department.

#### EQUALIZER BAR SUPPORT PIN

We are unable to give a standard recommendation for this component. Please contact our service department.

<b>PIVOT SHAFTS</b> Capacity: 40 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Oil Alcat 30	Gear Oil Alcat 50		

USE	CLIMATE	
Normal	Arctic	
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		



RECOIL SPRING HOUSING Capacity: 65 liter (each side)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Oil Alcat 30	Gear Oil Alcat 50		
Check every 500 hours			
USE		CLIMATE	
Normal		Arctic	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 10W			
Check every 500 hours			

TRACK ROLLER FRAME PIVOT BEARINGS			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Oil Alcat 30 Gear Oil Alcat 50			
USE		CLIMATE	
Normal		Arctic	

PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	

#### TRACK ROLLERS & IDLERS

We are unable to give a standard recommendation for this component. Please contact our service department.



TRAVEL REDUCTION UNIT Capacity: 12,5 liter (each hub)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 50			
Check every 250 hours, change every 200	0 hours/ 12 months		
USE		CLIMATE	
Normal		Cold	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 30			
Check every 250 hours, change every 200	0 hours/ 12 months		
USE		CLIMATE	
Severe		Cold	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Oil Alcat 30	Gear Oil Alcat 50		
Check every 250 hours, change every 200	0 hours/ 12 months		



WINCH HYDRAULIC DRIVE Capacity: 15 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 250 hours, change every 100	0 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 250 hours, change every 100	0 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Change every 500 hours		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 500 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.