## **CATERPILLAR FELLER BUNCHERS 2590**



use Normal		сымате Mediterranean	
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Check every 10 hours, change every	1 months/ 250 hours		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40		
Check every 10 hours, change every	1 months/ 250 hours		
USE		CLIMATE	
Alternative (acceptable)		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40		
Check every 10 hours, change every	1 months/ 250 hours		
USE		CLIMATE	

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40

Check every	10 hours.	change	every 1	months/	250 hours

Alternative (acceptable)

PRODUCT RECOMMENDATION 1

Synfleet SHPD 10W-40

Moderate

PRODUCT RECOMMENDATION 3 **Multifleet SHPD 10W-40** 

## **CATERPILLAR FELLER BUNCHERS 2590**



HYDRAULIC SYSTEM Capacity: 318 liter (Hydraulic tank)			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 30			
Check every 10 hours, change every	6 months/ 1000 hours		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30	
Check every 10 hours, change every	6 months/ 1000 hours	·	

HYDRAULIC SYSTEM VARIABLE PITCH FLEXXAIRE FAN Capacity: 0,65-1,22 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 50			
Check every 1000 hours, change every 48 months/ 6000 hours			
USE		CLIMATE	
Normal		Moderate	

Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 1000 hours, change every 48 months/ 6000 hours

COOLING SYSTEM Capacity: 36 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Check every 10 hours, change every	72 months/ 12000 hours	

## **CATERPILLAR FELLER BUNCHERS 2590**



SWING REDUCTION UNIT Capacity: 10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Change every 250 hours		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 250 hours		
TRAVEL REDUCTION UNIT Capacity: 6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.