

ENGINE C6.6 Acert Capacity: 21 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 3 months/ 500 hours

DIFFERENTIAL FRONT Capacity: 52 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 50 hours, change every 12 m	onths/ 2000 hours	

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	

Check every 50 hours, change every 12 months/ 2000 hours

USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	

Check every 50 hours, change every 12 months/ 2000 hours

USE	CLIMATE
Fluid analysis	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 50	

Check every 500 hours

USE	CLIMATE
Fluid analysis	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
Check every 500 hours	



USE	CLIMATE
Fluid analysis	Arctic
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	
Check every 500 hours	

DIFFERENTIAL REAR Capacity: 52 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50		
Check every 50 hours, change every 12 m	onths/ 2000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 50 hours, change every 12 m	onths/ 2000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 50 hours, change every 12 m	onths/ 2000 hours	
USE		CLIMATE
Fluid analysis		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 500 hours		
USE		CLIMATE
Fluid analysis		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 500 hours		
USE		CLIMATE
Fluid analysis		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 500 hours		



TRANSMISSION Capacity: 6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 10 hours, change every 3 months/ 500 hours

HYDRAULIC SYSTEM Capacity: 227 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 10W	Gear Oil Alcat 30	
Check every 10 hours, change every 2000 hours/ 12 months		

USE		CLIMATE
Fluid analysis		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 10W	Gear Oil Alcat 30	
Check every 500 hours		•

 GREASE POINTS/NIPPLES

 USE
 CLIMATE

 Normal
 Moderate

 PRODUCT RECOMMENDATION 1
 PRODUCT RECOMMENDATION 2
 PRODUCT RECOMMENDATION 3

 HT Q9 High Grade Grease
 Labora Grease
 MoS2 Grease EP 2

COOLING SYSTEM Capacity: 61 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Check every 10 hours, change every	72 months/ 12000 hours	



PUMP DRIVE Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 100 hours, change every 12 months/ 2000 hours		
USE		CLIMATE
Fluid analysis		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 500 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.