

ENGINE C6.6 Acert Capacity: 18 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Check every 10 hours, change every 3	months/ 500 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	
Charle avant 10 hours shangs success?	months/500 hours	
Check every 10 hours, change every 3		
DIFFERENTIAL	Honard, doo neard	
	Honard, doc nears	CLIMATE
DIFFERENTIAL	nontally doo nears	climate Moderate
DIFFERENTIAL USE	PRODUCT RECOMMENDATION 2	
DIFFERENTIAL use Normal		
DIFFERENTIAL use Normal PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2 Gear Oil Alcat 50	
DIFFERENTIAL use Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30	PRODUCT RECOMMENDATION 2 Gear Oil Alcat 50	
DIFFERENTIAL use Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Check every 10 hours, change every 3	PRODUCT RECOMMENDATION 2 Gear Oil Alcat 50	Moderate
DIFFERENTIAL USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Check every 10 hours, change every 3 USE	PRODUCT RECOMMENDATION 2 Gear Oil Alcat 50	Moderate
DIFFERENTIAL USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Check every 10 hours, change every 3 USE Normal	PRODUCT RECOMMENDATION 2 Gear Oil Alcat 50	Moderate

PRODUCT RECOMMENDATION 2

Gear Oil Alcat 50

Change every 100 hours

Initial service

Initial service

USE

PRODUCT RECOMMENDATION 1

Change every 100 hours

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W

Gear Oil Alcat 30

CLIMATE

CLIMATE

Arctic

Moderate



TANDEM DRIVE Capacity: 80 liter (each side)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 100 hours, c	hange every 24 months/ 2000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 100 hours, c	hange every 24 months/ 2000 hours	
TRANSMISSION		
Capacity: 47 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 10 hours, change every	3 months/ 500 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 10 hours, change every	3 months/ 500 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
	·	
Change every 100 hours		
		CLIMATE
Change every 100 hours use Initial service		climate Arctic
USE		
use Initial service		



HYDRAULIC SYSTEM Capacity: 55 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
01 1 0 11 (5001	10 11 100001	·	

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

CLIMATE
Moderate

Check every 10 hours, change every 72 months/ 12000 hours

CIRCLE DRIVE UNIT Capacity: 7 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 2000 hours/24 months

Change every 2000 hours/24 months		
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE



WHEEL SPINDLE HOUSINGS FRONT Capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 3 months/ 500 hours, change	every 24 months/ 2000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 3 months/ 500 hours, change every 24 months/ 2000 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.