## **CATERPILLAR RIGID DUMP TRUCKS 770**

(2008-2013)



ENGINE C15 Acert Capacity: 34 liter		
USE		CLIMATE
Preferred		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40	

Check every 10 hours, change every 3 months/ 500 hours

USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40

Check every 10 hours, change every 3 months/ 500 hours

USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Dieselfleet MSP 15W-40	

Check every 10 hours, change every 3 months/ 500 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40

Check every 10 hours, change every 3 months/ 500 hours

Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Alternative (acceptable)		Mediterranean
USE		CLIMATE

Check every 10 hours, change every 3 months/ 500 hours

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	

Check every 10 hours, change every 3 months/ 500 hours

# **DIFFERENTIAL REAR**Capacity: 114 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

### **CATERPILLAR RIGID DUMP TRUCKS 770**

(2008-2013)



	ī
Ľ	П
J	П
В	
$\mathbf{x}$	П
_	ı
u	J
u	П
u	$\sim$
ш	-
U	$\boldsymbol{\circ}$
И	м
Э.	•
к	3
-	
â٦	ΑΙ
N	П

Capacity: 22,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION + TORQUE CONVERTE Capacity: 95 liter	R	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change every 6 mo	nths/ 1000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 10 hours, change every 6 mo	nths/ 1000 hours	

HYDRAULIC SYSTEM HOIST + BRAK Capacity: 130 liter	E	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Charle avant 10 hours abance avant 6		

Check every 10 hours, change every 6 months/ 1000 hours

#### WHEEL BEARINGS FRONT

Capacity: 2,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 114 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 17	
Check every 10 hours, change every 72 m	12000 hours

#### **CATERPILLAR RIGID DUMP TRUCKS 770**

(2008-2013)



HYDRAULIC SYSTEM STEERING Capacity: 50 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change every	6 months/ 1000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Check every 10 hours, change every 6 months/ 1000 hours		
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Check every 10 hours, change every	6 months/ 1000 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.