

ENGINE 3508A Capacity: 91 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40

Check every 10 hours, change every 1 months/ 250 hours

USE	CLIMATE	
Normal	Mediterranean	
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 1 months/ 250 hours, change every 6 months/ 1000 hours		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 1 months/ 250 hours, change	6 months/ 1000 hours	
USE	CLIMATE	
Normal	Arctic	
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		



FINAL DRIVES		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours	
TRANSMISSION Powershift Capacity: 95 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 10 hours, change every 6 mg	onths/ 1000 hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 10 hours, change every 6 mg	onths/ 1000 hours	
GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		



WHEEL BEARINGS FRONT Capacity: 4,7 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 50	
Check every 1 months/ 250 hours	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
Check every 1 months/ 250 hours	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	
Check every 1 months/ 250 hours	
COOLING SYSTEM Capacity: 221 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	

Check every 10 hours, change every 24 months/ 3000 hours	
HOIST CONVERTER + BRAKE SYSTEM	
Capacity: 250 liter (Hydraulic tank)	

USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Oil Alcat 30	Gear Oil Alcat 50		
Check every 10 hours, change eve	ery 6 months/ 1000 hours		
USE		CLIMATE	
Normal		Cold	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 10W			

Coolant SP 17

Check every 10 hours, change every 6 months/ 1000 hours



HYDRAULIC SYSTEM STEERING Capacity: 83 liter (Hydraulic tank)			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 30			
Check every 10 hours, change every 6 months/ 1000 hours			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 10W			
Check every 10 hours, change every 6 months/ 1000 hours			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.