

# CATERPILLAR RIGID DUMP TRUCKS 795F AC ERM (2012 AND AFTER)



**ENGINE** C175-16  
Capacity: 312 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agridiesel MSP 15W-40</b>	<b>Dieselfleet MSP 15W-40</b>

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth MSP 10W-40</b>	<b>Armado Synth LSP Ultra 10W-40</b>

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Alternative (acceptable)	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Dieselfleet MSP 15W-40</b>		

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth MSP 10W-40</b>	<b>Agridiesel MSP 15W-40</b>

*Check every 10 hours, change every 3 months/ 500 hours*

## HUB REDUCTIONS REAR

Capacity: 246 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## HYDRAULIC SYSTEM HOIST + BRAKE

Capacity: 508 liter (Hydraulic tank), Capacity: 1500 liter (System)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

*Change every 2000 hours/ 12 months*

# CATERPILLAR RIGID DUMP TRUCKS 795F AC ERM (2012 AND AFTER)



## HYDRAULIC SYSTEM POWERED STAIRWAY

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Check every 3 months/ 500 hours, change every 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Fluid 3013***Check every 3 months/ 500 hours, change every 12 months*

## FAN DRIVE BEARINGS

We are unable to give a standard recommendation for this component. Please contact our service department.

## GREASE POINTS/NIPPLES OTHERS

USE	CLIMATE
Light Duty	Moderate

PRODUCT RECOMMENDATION 1

**HT Q9 High Grade Grease**

PRODUCT RECOMMENDATION 2

**Labora Grease**

USE	CLIMATE
Normal duty	Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

## LUBRICATING PUMP ELECTRIC AUTO LUBE SYSTEM

Capacity: 0,44 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 10W-40***Change every 2000 hours/ 12 months*

## WHEEL BEARINGS FRONT

Capacity: 64 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

# CATERPILLAR RIGID DUMP TRUCKS 795F AC ERM (2012 AND AFTER)

**COOLING SYSTEM**

Capacity: 1100 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Coolant SP 17***Check every 10 hours, change every 36 months/ 6000 hours***HYDRAULIC SYSTEM STEERING**

Capacity: 210 liter (Hydraulic tank), Capacity: 300 liter (System)

**USE**

Normal

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Gear Oil Alcat 30***Change every 2000 hours/ 12 months***USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 2****Dieselfleet CD+ 15W-40****PRODUCT RECOMMENDATION 3****Multifleet SHPD 15W-40***Change every 2000 hours/ 12 months***USE**

Biodegradable oil

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Perlus Biosynth 46***Change every 2000 hours/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.