

# CATERPILLAR SKID STEER LOADERS

## 262C CATERPILLAR C3.4 DIT (2008-2011)



**ENGINE C3.4 DIT**  
Capacity: 10 liter, Filter capacity: 1 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
|-------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

*Check every 250 hours, change every 500 hours/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2      |  |
|-----------------------------|-------------------------------|--|
| <b>Agrisynth LSP 10W-40</b> | <b>Multifleet SHPD 10W-40</b> |  |

*Check every 250 hours, change every 500 hours/ 12 months*

**HYDRAULIC SYSTEM HYDROSTATIC DRIVE**  
Capacity: 39 liter (Hydraulic tank)

| USE       | CLIMATE  |
|-----------|----------|
| Preferred | Moderate |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Gear Oil Alcat 10W</b> |  |  |

*Check every 10 hours, change every 2000 hours/ 12 months*

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Gear Oil Alcat 30</b> |  |  |

*Check every 10 hours, change every 2000 hours/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Gear Oil Alcat 10W</b> |  |  |

*Check every 10 hours, change every 2000 hours/ 12 months*

| USE                      | CLIMATE  |
|--------------------------|----------|
| Alternative (acceptable) | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
|-------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

*Check every 10 hours, change every 2000 hours/ 12 months*

# CATERPILLAR SKID STEER LOADERS

## 262C CATERPILLAR C3.4 DIT (2008-2011)



| USE   |  | CLIMATE  |
|---|--|----------|
| Biodegradable oil   |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Perlus Biosynth 46</b>                                       |  |          |
| <i>Check every 10 hours, change every 2000 hours/ 12 months</i> |  |          |

### EXTERNAL GREASE POINTS

We are unable to give a standard recommendation for this component. Please contact our service department.

| COOLING SYSTEM                             |  |          |
|--|--|----------|
| Capacity: 13,9 liter                       |  |          |
| USE  |  | CLIMATE  |
| Normal                                     |  | Moderate |
| PRODUCT RECOMMENDATION 1                   |  |          |
| <b>Coolant SP 17</b>                       |  |          |
| <i>Change every 12000 hours/ 72 months</i> |  |          |

| DRIVE CHAIN CASE   |                               |                               |
|--|-------------------------------|-------------------------------|
| Capacity: 10 liter   |                               |                               |
| USE  |                               | CLIMATE                       |
| Preferred  |                               | Mediterranean                 |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Agridiesel CRD+ 15W-40</b>                                      | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |
| Check every 3 months/ 500 hours, change every 6 months/ 1000 hours |                               |                               |
| USE  |                               | CLIMATE                       |
| Preferred  |                               | Moderate                      |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2      |                               |
| <b>Agrisynth LSP 10W-40</b>  | <b>Multifleet SHPD 10W-40</b> |                               |
| Check every 3 months/ 500 hours, change every 6 months/ 1000 hours |                               |                               |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.