

CATERPILLAR TRACKED EXCAVATORS

215C 4HG (1985-1990)

**ENGINE**

Capacity: 19 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	Multifleet SCD 30	

Change every 250 hours/ 1 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Change every 250 hours/ 1 months

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

*Change every 250 hours/ 1 months***FINAL DRIVES**

Capacity: 15 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 50	Multifleet SCD 40	

Check every 1 months/ 250 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Check every 1 months/ 250 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Check every 1 months/ 250 hours

CATERPILLAR TRACKED EXCAVATORS

215C 4HG (1985-1990)



HYDRAULIC SYSTEM

Capacity: 155 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Change every 6 months/ 2000 hours*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Change every 6 months/ 2000 hours*

GREASE POINTS/NIPPLES

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2

COOLING SYSTEM

Capacity: 27 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 17*Change every 6 months/ 2000 hours*

CATERPILLAR TRACKED EXCAVATORS

215C 4HG (1985-1990)



SWING REDUCTION UNIT

Capacity: 29 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 50	Multifleet SCD 40	

Check every 1 months/ 250 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Check every 1 months/ 250 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Check every 1 months/ 250 hours

TRACK PINS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

TRACK ROLLERS & IDLERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.