

ENGINE Mitsubishi 4D34-TE1 Capacity: 17 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Change every 250 hours/ 1 months	·	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	
Change every 250 hours/ 1 months		

FINAL DRIVES		
Capacity: 2,5 liter (each hub)		A
Normal		CLIMATE Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 1 months/ 250 hours, change	e every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 1 months/ 250 hours, change	e every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	e every 12 months/ 2000 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Change every 250 hours		



USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 250 hours		
HYDRAULIC SYSTEM Capacity: 88 liter (Reservoir), Capacit	y: 190 liter (System)	
USE	· · · ·	CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Change every 2000 hours/ 12 months	3	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agridiesel CRD+ 15W-40	Agrifluid Synth XHP Ultra
Change every 2000 hours/ 12 months	5	
JSE		CLIMATE
50% use of breaker		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Change every 1000 hours		
use 50% use of breaker		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agridiesel CRD+ 15W-40	Agrifluid Synth XHP Ultra
Change every 1000 hours		,
JSE		CLIMATE
100% use of breaker		Mediterranean
PRODUCT RECOMMENDATION 1		
PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30		
Gear Oil Alcat 30 Change every 600 hours USE		Mediterranean
Gear Oil Alcat 30 Change every 600 hours use 100% use of breaker		Mediterranean CLIMATE Moderate
100% use of breaker PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 600 hours USE 100% use of breaker PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40	PRODUCT RECOMMENDATION 2 Agridiesel CRD+ 15W-40	Mediterranean



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM Capacity: 1,5 liter (Reservoir), Capacity: 17 liter (System)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Change every 6000 hours/ 72 months		

PIVOT SHAFT BEARINGS	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 50	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	



RECOIL SPRING COMPARTMENT		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
	1	I
SWING REDUCTION UNIT Capacity: 2,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
	Geal Oil Alcat 30	
Change every 250 hours/ 1 months	Geal Oil Alcat 30	
	Geal Oil Alcat 30	CLIMATE
Change every 250 hours/ 1 months	Geal Oil Alcat 30	CLIMATE Arctic
Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 1	Geal Oil Alcat 30	
Change every 250 hours/ 1 months USE Normal	Geal Oil Alcat 30	
Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 1	Geal Oil Alcat 30	
Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours/ 1 months USE	Geal Oil Alcat 30	Arctic
Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours/ 1 months	Geal Oil Alcat 30	Arctic
Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours/ 1 months USE Initial service PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	Arctic
Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours/ 1 months USE Initial service		Arctic
Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours/ 1 months USE Initial service PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	Arctic
Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours/ 1 months USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 250 hours USE	PRODUCT RECOMMENDATION 2	CLIMATE Moderate CLIMATE
Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours/ 1 months USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 250 hours USE Initial service	PRODUCT RECOMMENDATION 2	Arctic CLIMATE Moderate
Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours/ 1 months USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	CLIMATE Moderate CLIMATE
Change every 250 hours/ 1 months USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours/ 1 months USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 250 hours USE Initial service	PRODUCT RECOMMENDATION 2	CLIMATE Moderate CLIMATE

TRACK IDI ERS

CATERPILLAR TRACKED EXCAVATORS 313B CR BAS (1996-2004)



TRACK IDEERO		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
TRACK ROLLER FRAME		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
TRACK ROLLERS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
	•	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.