PRODUCT RECOMMENDATION

# CATERPILLAR TRACKED EXCAVATORS
# 316E L WZY (2011 AND AFTER)

**ENGINE** C4.4 Acert
Capacity: 16 liter

| USE | | CLIMATE |
|---|---|---|
| Preferred | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Agridiesel MSP 15W-40** | **Dieselfleet MSP 15W-40** | |
| *Check every 10 hours, change every 3 months/ 500 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Preferred | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Dieselfleet LSP Ultra 10W-30** | **Dieselfleet MSP 10W-30** | |
| *Check every 10 hours, change every 3 months/ 500 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Alternative (acceptable) | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Agrisynth MSP 10W-40** | **Dieselfleet MSP 15W-40** | |
| *Check every 10 hours, change every 3 months/ 500 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Alternative (acceptable) | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Agrisynth LSP Ultra FE 5W-30** | **Agridiesel MSP 15W-40** | **Dieselfleet LSP Ultra 10W-30** |
| *Check every 10 hours, change every 3 months/ 500 hours* | | |

**HYDRAULIC SYSTEM**
Capacity: 190 liter (Change capacity)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | | |
| **Gear Oil Alcat 30** | | |
| *Check every 10 hours, change every 18 months/ 3000 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Agridiesel CRD+ 15W-40** | **Agrifluid HT-Plus** | **Kroontrak MTH 10W-30** |
| *Check every 10 hours, change every 18 months/ 3000 hours* | | |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# CATERPILLAR TRACKED EXCAVATORS
# 316E L WZY (2011 AND AFTER)

| USE | | CLIMATE |
|---|---|---|
| Partial hammer use (50%) | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| **Gear Oil Alcat 30** | | |
| *Check every 10 hours, change every 1000 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Partial hammer use (50%) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Agridiesel CRD+ 15W-40** | **Agrifluid HT-Plus** | **Kroontrak MTH 10W-30** |
| *Check every 10 hours, change every 1000 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Full time hammer use (100%) | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| **Gear Oil Alcat 30** | | |
| *Check every 10 hours, change every 600 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Full time hammer use (100%) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Agridiesel CRD+ 15W-40** | **Agrifluid HT-Plus** | **Kroontrak MTH 10W-30** |
| *Check every 10 hours, change every 600 hours* | | |

**COOLING SYSTEM**
Capacity: 30 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Coolant SP 17** | | |
| *Check every 10 hours, change every 36 months/ 6000 hours* | | |

**SWING GEAR**
Capacity: 18 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |
| *Change every 2000 hours/ 12 months* | | |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# CATERPILLAR TRACKED EXCAVATORS
# 316E L WZY (2011 AND AFTER)

**SWING REDUCTION UNIT**
Capacity: 2,4 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Gear Oil Alcat 30** | **Gear Oil Alcat 50** | |
| *Check every 1 months/ 250 hours, change every 6 months/ 1000 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Normal | | Arctic |
| **PRODUCT RECOMMENDATION 1** | | |
| **Gear Oil Alcat 10W** | | |
| *Check every 1 months/ 250 hours, change every 6 months/ 1000 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Gear Oil Alcat 30** | **Gear Oil Alcat 50** | |
| *Change every 250 hours/ 6 months* | | |

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Arctic |
| **PRODUCT RECOMMENDATION 1** | | |
| **Gear Oil Alcat 10W** | | |
| *Change every 250 hours/ 6 months* | | |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# CATERPILLAR TRACKED EXCAVATORS
# 316E L WZY (2011 AND AFTER)

**TRAVEL REDUCTION UNIT**
Capacity: 5 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Gear Oil Alcat 30** | **Gear Oil Alcat 50** | |

*Check every 1 months/ 250 hours, change every 12 months/ 2000 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Arctic |
| **PRODUCT RECOMMENDATION 1** | | |
| **Gear Oil Alcat 10W** | | |

*Check every 1 months/ 250 hours, change every 12 months/ 2000 hours*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Gear Oil Alcat 30** | **Gear Oil Alcat 50** | |

*Change every 250 hours/ 6 months*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Arctic |
| **PRODUCT RECOMMENDATION 1** | | |
| **Gear Oil Alcat 10W** | | |

*Change every 250 hours/ 6 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367