CATERPILLAR TRACKED EXCAVATORS 320B LL 9JS (1996-2000)



PRODUCT RECOMMENDATION 1 Synfleet SHPD 10W-40	PRODUCT RECOMMENDATION 2 Multifleet SHPD 10W-40	
Initial service		Moderate
USE		CLIMATE
Change every 100 hours		
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Initial service		Mediterranean
USE		CLIMATE
Change every 250 hours/ 1 months		
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE
Change every 250 hours/ 1 months		
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Mediterranean
USE		CLIMATE

CATERPILLAR TRACKED EXCAVATORS 320B LL 9JS (1996-2000)



FINAL DRIVES		
Capacity: 10 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, cha	nge every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, cha	nge every 12 months/ 2000 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Change every 250 hours		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 250 hours		
HYDRAULIC SYSTEM		
Capacity: 130 liter (Reservoir), Capacit	y: 280 liter (System)	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

Change every 2000 hours/ 12 months

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

Change every 2000 hours/ 12 months

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 3

Agrifluid Synth XHP Ultra

CATERPILLAR TRACKED EXCAVATORS 320B LL 9JS (1996-2000)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

CLIMATE
Moderate

Change every 12000 hours/72 months

SWING GEAR				
use Normal		CLIMATE		
		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		
Check every 12 months/ 2000 hour	s	1		

CATERPILLAR TRACKED EXCAVATORS 320B LL 9JS (1996-2000)



USE NOTICE PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Check every 1 months/ 250 hours, change every 6 months/ 1000 hours USE NOTICE PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 1 months/ 250 hours, change every 6 months/ 1000 hours USE NOTICE PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 1 months/ 250 hours, change every 6 months/ 1000 hours USE Initial service PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Gear Oil Alcat 30 Change every 250 hours USE CLIMATE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Change every 250 hours TRACK IDLERS USE NOTICE PRODUCT RECOMMENDATION 1 Multifleet SCD 30 TRACK ROLLERS USE NOTICE USE NOTICE CLIMATE NOTICE Moderate CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate	SWING REDUCTION UNIT Capacity: 6 liter		
PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Check every 1 months/ 250 hours, change every 6 months/ 1000 hours USE Normal Gear Oil Alcat 10W Check every 1 months/ 250 hours, change every 6 months/ 1000 hours USE ROTH 1 months/ 250 hours, change every 6 months/ 1000 hours USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 2 Gear Oil Alcat 50 CLIMATE Moderate CLIMATE Moderate CLIMATE Arctic PRODUCT RECOMMENDATION 2 Gear Oil Alcat 50 Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours TRACK IDLERS USE Normal Moderate CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate	USE		CLIMATE
Gear Oil Alcat 30 Check every 1 months/ 250 hours, change every 6 months/ 1000 hours USE Normal CLIMATE Arctic PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 1 months/ 250 hours, change every 6 months/ 1000 hours USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 2 Gear Oil Alcat 50 Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours TRACK IDLERS USE Normal TRACK ROLLERS USE Normal TRACK ROLLERS USE Normal CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate	Normal		Moderate
Check every 1 months/250 hours, change every 6 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 1 months/250 hours, change every 6 months/ 1000 hours USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 250 hours USE USE CLIMATE Moderate CLIMATE Initial service PRODUCT RECOMMENDATION 2 Gear Oil Alcat 50 Change every 250 hours USE CLIMATE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours TRACK IDLERS USE Normal TRACK ROLLERS USE Normal CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 1 months/ 250 hours, change every 6 months/ 1000 hours USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours USE TRACK IDLERS USE Normal Multifleet SCD 30 TRACK ROLLERS USE Normal Moderate CLIMATE Moderate Moderate CLIMATE Moderate Moderate	Gear Oil Alcat 30	Gear Oil Alcat 50	
Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 1 months/ 250 hours, change every 6 months/ 1000 hours USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 2 Gear Oil Alcat 50 Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours TRACK IDLERS USE Normal TRACK ROLLERS USE Normal TRACK ROLLERS USE Normal TRACK ROLLERS USE Normal Multifleet SCD 30	Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours	
PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 1 months/ 250 hours, change every 6 months/ 1000 hours USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 CLIMATE Arctic PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours USE INITIAL SERVICE PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours TRACK IDLERS USE Normal Multifleet SCD 30 TRACK ROLLERS USE Normal Moderate CLIMATE Moderate Moderate CLIMATE Moderate Moderate CLIMATE Moderate Moderate			
Gear Oil Alcat 10W Check every 1 months/ 250 hours, change every 6 months/ 1000 hours USE Initial Service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 250 hours USE Initial Service PRODUCT RECOMMENDATION 2 Gear Oil Alcat 50 CLIMATE Initial Service Arctic PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours TRACK IDLERS USE Normal Multifleet SCD 30 TRACK ROLLERS USE Normal TRACK ROLLERS USE Normal Moderate CLIMATE Moderate Moderate	Normal		Arctic
Check every 1 months/ 250 hours, change every 6 months/ 1000 hours USE Initial Service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 250 hours USE Initial Service PRODUCT RECOMMENDATION 2 Gear Oil Alcat 50 CLIMATE Initial Service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours TRACK IDLERS USE Normal Multifleet SCD 30 TRACK ROLLERS USE Normal TRACK ROLLERS USE Normal Moderate CLIMATE Moderate Moderate CLIMATE Moderate Moderate			
USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 CLIMATE Arctic PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours TRACK IDLERS USE Normal TRACK COMMENDATION 1 Multifleet SCD 30 TRACK ROLLERS USE CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate	Gear Oil Alcat 10W		
Initial service Moderate PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours TRACK IDLERS USE Normal TRACK ROLLERS USE TRACK ROLLERS USE Normal TRACK ROLLERS USE Normal TRACK ROLLERS USE Normal Multifleet SCD 30 TRACK ROLLERS USE Normal Moderate	Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours	
PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Gear Oil Alcat 50 Change every 250 hours USE Initial Service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours TRACK IDLERS USE Normal TRACK ROLLERS USE CLIMATE Moderate CLIMATE Arctic			CLIMATE
Gear Oil Alcat 30 Change every 250 hours USE Initial Service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours TRACK IDLERS USE Normal TRACK ROLLERS USE CLIMATE Moderate TRACK ROLLERS USE Normal TRACK ROLLERS USE Normal CLIMATE Moderate Moderate CLIMATE Moderate Moderate	Initial service		Moderate
Change every 250 hours USE Initial service Arctic PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours TRACK IDLERS USE Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 30 TRACK ROLLERS USE CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
USE Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours TRACK IDLERS USE Normal Multifleet SCD 30 TRACK ROLLERS USE CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate	Gear Oil Alcat 30	Gear Oil Alcat 50	
Initial service Arctic PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours TRACK IDLERS USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 Multifleet SCD 30 TRACK ROLLERS USE CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate	Change every 250 hours		
PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours TRACK IDLERS USE Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 30 TRACK ROLLERS USE CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate	USE		CLIMATE
Gear Oil Alcat 10W Change every 250 hours TRACK IDLERS USE Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 30 TRACK ROLLERS USE USE USE USE USE USE USE	Initial service		Arctic
TRACK IDLERS USE Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 30 TRACK ROLLERS USE USE USE USE USE USE USE	PRODUCT RECOMMENDATION 1		
TRACK IDLERS USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 Multifleet SCD 30 TRACK ROLLERS USE CLIMATE Normal Moderate CLIMATE Moderate	Gear Oil Alcat 10W		
USE Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 30 TRACK ROLLERS USE Normal CLIMATE Moderate CLIMATE Moderate	Change every 250 hours		
USE Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 30 TRACK ROLLERS USE Normal CLIMATE Moderate CLIMATE Moderate			
Normal Moderate PRODUCT RECOMMENDATION 1 Multifleet SCD 30 TRACK ROLLERS USE CLIMATE Normal Moderate			
PRODUCT RECOMMENDATION 1 Multifleet SCD 30 TRACK ROLLERS USE Normal CLIMATE Moderate			
TRACK ROLLERS USE Normal CLIMATE Moderate	Normal	_	Moderate
TRACK ROLLERS USE CLIMATE Normal Moderate			
Normal CLIMATE Moderate	Multifleet SCD 30		
Normal CLIMATE Moderate			
Normal Moderate	TRACK ROLLERS		
	Normal		Moderate
Multifleet SCD 30	PRODUCT RECOMMENDATION 1		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.