

CATERPILLAR UNDERGROUND ARTICULATED TRUCKS AD40 SERIES II 1YZ (TILL 2005)



ENGINE 3408E
Capacity: 45,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 3

Synfleet SHPD 10W-40

Check every 10 hours, change every 1 months/ 250 hours

DIFFERENTIAL FRONT

Capacity: 95 liter (+ hub reductions)

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR

Capacity: 95 liter (+ hub reductions)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION

Capacity: 85 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 50

Check every 10 hours, change every 6 months/ 1000 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

Check every 10 hours, change every 6 months/ 1000 hours

USE
Normal

CLIMATE
Cold

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W

Check every 10 hours, change every 6 months/ 1000 hours

CATERPILLAR UNDERGROUND ARTICULATED TRUCKS AD40 SERIES II 1YZ (TILL 2005)

**HYDRAULIC SYSTEM HOIST + BRAKE**

Capacity: 465 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 10 hours, change every 6 months/ 1000 hours

GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 145 liter

USE		CLIMATE
Preferred, extended		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 10 hours, change every 48 months/ 6000 hours

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 24 months/ 3000 hours

HYDRAULIC SYSTEM STEERING

Capacity: 84 liter (Hydraulic tank), Capacity: 120 liter (System)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 10 hours, change every 6 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.