CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CB-335E SERIES II C3C



(2006 AND AFTER)

ENGINE Caterpillar 3024C Capacity: 10,6 liter			
USE		CLIMATE	
Preferred		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrisynth LSP 10W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	
Check every 10 hours, change every 500 hours/ 6 months			
USE		CLIMATE	
Alternative (acceptable)		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40		
Check every 10 hours, change every 250 hours/ 3 months			
USE		CLIMATE	
Alternative (acceptable)		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40	
Check every 10 hours, change every	250 hours/ 3 months	·	

HYDRAULIC SYSTEM Capacity: 48 liter (Hydraulic tank)			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Multifleet SCD 30	Gear Oil Alcat 30		
Check every 10 hours, change every 1000 hours/ 12 months			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Helar 0W-40	Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	
Check every 10 hours, change every 1000 hours/ 12 months			
USE		CLIMATE	
Biodegradable oil		Moderate	
PRODUCT RECOMMENDATION 1			
Perlus Biosynth 46			
Check every 10 hours, change every 1000 hours/ 12 months			

PRODUCT RECOMMENDATION

CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CB-335E SERIES II C3C



(2006 AND AFTER)

GREASE POINTS/NIPPLES				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
MoS2 Grease EP 2				

COOLING SYSTEM Capacity: 9,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 17	

Check every 10 hours, change every 36 months/ 6000 hours

VIBRATORY UNIT Capacity: 2,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Abacot MEP HD 220	
Change every 3000 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.