

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CC24 241 (2009-2013)



ENGINE C1.5
Capacity: 6 liter

USE	CLIMATE
Preferred, extended	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Fluid analysis, preferred	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Check every 250 hours

USE	CLIMATE
Alternative (acceptable)	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 250 hours

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40

Check every 10 hours, change every 250 hours

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CC24 241 (2009-2013)



HYDRAULIC SYSTEM

Capacity: 26,6 liter (Hydraulic tank)

USE		CLIMATE
Fluid analysis, biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 12 months/ 500 hours

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 10 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 10 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Fluid analysis, alternative		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 12 months/ 500 hours

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CC24 241 (2009-2013)



COOLING SYSTEM

Capacity: 6 liter

USE		CLIMATE
Fluid analysis, preferred		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 12 months, change every 72 months/ 12000 hours

USE		CLIMATE
Fluid analysis, initial (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 500 hours

USE		CLIMATE
Fluid analysis, alternative		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 250 hours

ECCENTRIC WEIGHT HOUSING

Capacity: 2 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP HD 220		

Change every 3000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.