

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CS-573E CEB/CNN (2003 AND AFTER)



ENGINE Caterpillar 3056E ATAAC
Capacity: 12,1 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 500 hours/ 6 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40

Check every 10 hours, change every 500 hours/ 6 months

DIFFERENTIAL

Capacity: 14,5 liter, Capacity: 0,5 liter (special additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

FINAL DRIVES

Capacity: 1,75 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 50	

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 50	

Change every 250 hours/ 6 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	

Change every 250 hours/ 6 months

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CS-573E CEB/CNN (2003 AND AFTER)



HYDRAULIC SYSTEM

Capacity: 64 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

PRODUCT RECOMMENDATION 2

Gear Oil Alcat 30*Check every 10 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3

Kroontrak MTH 10W-30*Check every 10 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46*Check every 10 hours, change every 1000 hours/ 12 months*

COOLING SYSTEM

Capacity: 26 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 17*Check every 10 hours, change every 36 months/ 3000 hours*

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CS-573E CEB/CNN (2003 AND AFTER)

**DRUM COOLING**

Capacity: 21 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
AgriDiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

ECCENTRIC WEIGHT HOUSING

Capacity: 13 liter (each)

USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP HD 220		

Change every 36 months/ 3000 hours

USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		

Change every 36 months/ 3000 hours

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CS-573E CEB/CNN (2003 AND AFTER)



PLANETARY DRUM DRIVE

Capacity: 4,3 liter

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1

Abacot MEP HD 220*Check every 3 months/ 250 hours, change every 12 months/ 1000 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Abacot MEP HD 220*Change every 250 hours/ 6 months*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

Abacot MEP Synth 220

PRODUCT RECOMMENDATION 2

Abacot MEP 220*Check every 3 months/ 250 hours, change every 12 months/ 1000 hours*

USE	CLIMATE
Initial service (alternative)	Moderate

PRODUCT RECOMMENDATION 1

Abacot MEP Synth 220

PRODUCT RECOMMENDATION 2

Abacot MEP 220*Change every 250 hours/ 6 months*

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CS-573E CEB/CNN (2003 AND AFTER)

**VIBRATORY SUPPORT**

Capacity: 0,85 liter

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1

Abacot MEP HD 220*Check every 3 months/ 250 hours, change every 12 months/ 1000 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Abacot MEP HD 220*Change every 250 hours/ 6 months*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

Abacot MEP Synth 220

PRODUCT RECOMMENDATION 2

Abacot MEP 220*Check every 3 months/ 250 hours, change every 12 months/ 1000 hours*

USE	CLIMATE
Initial service (alternative)	Moderate

PRODUCT RECOMMENDATION 1

Abacot MEP Synth 220

PRODUCT RECOMMENDATION 2

Abacot MEP 220*Change every 250 hours/ 6 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.