

(2003 AND AFTER)

ENGINE Caterpillar 3056E ATAAC Capacity: 13,6 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40		
Check every 10 hours, change every 500 hours/ 6 months			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40	
Check every 10 hours, change every 500	hours/ 6 months		

#### **DIFFERENTIAL**

Capacity: 17 liter, Capacity: 0,5 liter (special additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

FINAL DRIVES Capacity: 3,5 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 50			
Check every 3 months/ 250 hours, change	every 12 months/ 1000 hours		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 30			
Check every 3 months/ 250 hours, change	every 12 months/ 1000 hours		
USE		CLIMATE	
Initial service		Mediterranean	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 50			
Change every 250 hours/ 6 months			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 30			
Change every 250 hours/ 6 months			



(2003 AND AFTER)

HYDRAULIC SYSTEM Capacity: 64 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Check every 10 hours, change every 1000 hours/ 12 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 10 hours, change every 1000 hours/ 12 months		
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Check every 10 hours, change every 1000 hours/ 12 months		

COOLING SYSTEM Capacity: 26 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Check every 10 hours, change every 36 months/ 3000 hours		



(2003 AND AFTER)

DRUM COOLING Capacity: 21 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

ECCENTRIC WEIGHT HOUSING Capacity: 13 liter (each)		
USE	CLIMATE	
Preferred	Moderate	
PRODUCT RECOMMENDATION 1		
Abacot MEP HD 220		
Change every 36 months/ 3000 hours		
USE	CLIMATE	
Alternative (acceptable)	Mediterranean	
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Change every 36 months/ 3000 hours		



(2003 AND AFTER)

PLANETARY DRUM DRIVE Capacity: 4,3 liter		
USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP HD 220		
Check every 3 months/ 250 hours, o	change every 12 months/ 1000 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP HD 220		
Change every 250 hours/ 6 months		
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Abacot MEP Synth 220	Abacot MEP 220	
Check every 3 months/250 hours, of	change every 12 months/ 1000 hours	
USE		CLIMATE
Initial service (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Abacot MEP Synth 220	Abacot MEP 220	
Change every 250 hours/ 6 months		



(2003 AND AFTER)

VIBRATORY SUPPORT Capacity: 0,95 liter		
USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP HD 220		
Check every 3 months/ 250 hours, change	every 12 months/ 1000 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP HD 220		
Change every 250 hours/ 6 months		
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Abacot MEP Synth 220	Abacot MEP 220	
Check every 3 months/ 250 hours, change every 12 months/ 1000 hours		
USE		CLIMATE
Initial service (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Abacot MEP Synth 220	Abacot MEP 220	
Change every 250 hours/ 6 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.