

CATERPILLAR WHEELED EXCAVATORS M315 7ML



ENGINE
Capacity: 9 liter

| | |
|--------|---------------|
| USE | CLIMATE |
| Normal | Mediterranean |

| | | |
|-------------------------------|-------------------------------|-------------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Change every 250 hours

| | |
|--------|----------|
| USE | CLIMATE |
| Normal | Moderate |

| | | |
|-----------------------------|-------------------------------|--|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Synfleet SHPD 10W-40 | Multifleet SHPD 10W-40 | |

Change every 250 hours

DIFFERENTIAL FRONT
Capacity: 8 liter

| | |
|--------|---------------|
| USE | CLIMATE |
| Normal | Mediterranean |

| | | |
|--------------------------------|-------------------------------------|--|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube Racing 75W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Check every 500 hours, change every 2000 hours

| | |
|--------|----------|
| USE | CLIMATE |
| Normal | Moderate |

| | | |
|---------------------------|--|--|
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube LS 80W-90 | | |

Check every 500 hours, change every 2000 hours

DIFFERENTIAL REAR
Capacity: 11 liter

| | |
|--------|---------------|
| USE | CLIMATE |
| Normal | Mediterranean |

| | | |
|--------------------------------|-------------------------------------|--|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube Racing 75W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Check every 500 hours, change every 2000 hours

| | |
|--------|----------|
| USE | CLIMATE |
| Normal | Moderate |

| | | |
|---------------------------|--|--|
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube LS 80W-90 | | |



CATERPILLAR WHEELED EXCAVATORS M315 7ML



HUB REDUCTIONS (DRUM BRAKES)

Capacity: 1,2 liter (each hub)

| USE | | CLIMATE |
|--------------------------------|-------------------------------------|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube Racing 75W-140 | Unigear LS GL-3/GL-5 85W-140 | |

| USE | | CLIMATE |
|---------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube LS 80W-90 | | |

HUB REDUCTIONS (WET BRAKES)

Capacity: 2 liter (each hub)

| USE | | CLIMATE |
|--------------------------------|-------------------------------------|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube Racing 75W-140 | Unigear LS GL-3/GL-5 85W-140 | |

| USE | | CLIMATE |
|---------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube LS 80W-90 | | |

TRANSMISSION

Capacity: 3 liter

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |

Check every 500 hours, change every 2000 hours

| USE | | CLIMATE |
|-----------------------------|-----------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 |

Check every 500 hours, change every 2000 hours

CATERPILLAR WHEELED EXCAVATORS M315 7ML



HYDRAULIC SYSTEM

Capacity: 200 liter

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Gear Oil Alcat 30 | | |

Check every 500 hours, change every 2000 hours

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Gear Oil Alcat 10W | | |

Check every 500 hours, change every 2000 hours

| USE | CLIMATE |
|--------------------------|----------|
| Alternative (acceptable) | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Perlus Biosynth 46 | | |

Check every 500 hours, change every 2000 hours

GREASE POINTS/NIPPLES

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| MoS2 Grease EP 2 | | |

COOLING SYSTEM

Capacity: 27 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Coolant SP 17 | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.