

# DOOSAN (DAEWOO) TRACKED EXCAVATORS SOLAR, S-SERIES SOLAR 225 LC-V DAEWOO DB58TIS (2006-2008)



**ENGINE** Daewoo DB58TIS  
Capacity: 19 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3     |
|-----------------------------|-----------------------------|------------------------------|
| <b>Kroontrak CVT 10W-40</b> | <b>Agrisynth MSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> |

*Change every 250 hours/ 6 months*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3     |
|-----------------------------|-----------------------------|------------------------------|
| <b>Kroontrak CVT 10W-40</b> | <b>Agrisynth MSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> |

*Change every 50 hours*

**HYDRAULIC SYSTEM**  
Capacity: 240 liter (Tank)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
|--------------------------|--------------------------|--|
| <b>Perlus H 46</b>       | <b>Perlus H 32</b>       |  |

*Change every 2000 hours*

## GREASE POINTS/NIPPLES

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
|--------------------------|---------------------------------|------------------------------|
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

**COOLING SYSTEM**  
Capacity: 42 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |  |
|-------------------------------|--------------------------|--|
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |  |

*Change every 2000 hours*

# DOOSAN (DAEWOO) TRACKED EXCAVATORS SOLAR, S-SERIES SOLAR 225 LC-V DAEWOO DB58TIS (2006-2008)

**SWING REDUCTION UNIT**

Capacity: 5 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Change every 2000 hours***TRAVEL REDUCTION UNIT**

Capacity: 5,4 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Change every 2000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*